

# TECHNICAL INFORMATION SHEET

## CON3005 Wyndham Oak

### Contemporary Collection



#### Product Information

|                     |                             |
|---------------------|-----------------------------|
| <b>Product Name</b> | Wyndham Oak                 |
| <b>Product Code</b> | CON3005                     |
| <b>Collection</b>   | Contemporary                |
| <b>Construction</b> | Engineered                  |
| <b>Size</b>         | 18 x 190 x 1900mm           |
| <b>Pack Size</b>    | 2.17m <sup>2</sup>          |
| <b>Grade</b>        | Rustic                      |
| <b>Surface</b>      | Handscraped<br>& Undulating |
| <b>Finish</b>       | Natural Oiled               |
| <b>Profile</b>      | T&G                         |
| <b>Edge</b>         | Bevelled                    |
| <b>Pattern</b>      | Plank                       |
| <b>Thickness</b>    | 18mm                        |
| <b>Width</b>        | 190mm                       |
| <b>Length</b>       | 1900mm                      |
| <b>Wear Layer</b>   | 4mm                         |
| <b>Backing</b>      | Eucalyptus                  |
| <b>Top Layer</b>    | Oak                         |

#### Technical Information

|                                    |             |
|------------------------------------|-------------|
| <b>Formaldehyde Emissions</b>      | E1          |
| <b>Pentachlorophenol Emissions</b> | ≤5ppm       |
| <b>Thermal Conductivity</b>        | 0.13W/(M.K) |
| <b>Slip Resistance PTV</b>         | 52/26       |
| <b>Fire Classification</b>         | Dfl-s1      |
| <b>Moisture Content</b>            | 6-9%        |
| <b>Hardness Rating</b>             | 1.8kn       |

#### Additional Information

|                        |     |
|------------------------|-----|
| <b>UKTR Compliance</b> | Yes |
|------------------------|-----|

#### Grading Information

Rustic grade has the potential to include all characteristics across the majority of boards with knots appearing in varying sizes as well as colour variation in the timber to be expected. Sapwood is possible, checks that are likely to be present will be filled in a colour to complement the natural look of the timber.

#### Installation and Warranty

Atkinson & Kirby recommend that all floors are installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fitting instructions that can be found on our website.

#### Installation Method

|                           |     |
|---------------------------|-----|
| <b>Floated</b>            | Yes |
| <b>Secret Nailed</b>      | Yes |
| <b>Stuck Down</b>         | Yes |
| <b>Underfloor Heating</b> | Yes |

#### Recommended Care and Maintenance Products\*

|                          |  |
|--------------------------|--|
| <b>For Regular Care</b>  | WOCA Natural Soap  |
| <b>For Monthly Care</b>  | WOCA Oil Refresher Soap                                    |
| <b>Every 6-12 Months</b> | WOCA Maintenance Gel &<br>WOCA Intensive Cleaner as primer |

\*Remember to patch test any cleaning or finishing products before using on the whole length of your floor.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.

Floors that define your space  
Tel: 01695 573234 | Scotland T: 01506 505030 | sales@akirby.co.uk | www.akirby.co.uk