TECHNICAL INFORMATION SHEET

PAR1008 Sloane Smoked Oak Parquet Collection





Product Information

Product Name
Product Code
PAR1008
Collection
Parquet
Construction
Size
Sloane Smoked Oak
PAR1008
Parquet
Engineered
11 x 70 x 500mm

Pack Size1.68m²GradeSelectSurfaceSmooth

Finish Natural Oil Protect

Profile T&G

Edge Square Edge

PatternBlockThickness11mmWidth70mmLength500mmWear Layer3.6mm

Backing Spruce Staves

Top Layer Oak

Technical Information

Formaldehyde Emissions E1

Pentachlorophenol Emissions Not Detectable
Thermal Conductivity RT = 0,078 m²K/W

Slip Resistance PTV 59/27

Fire Classification Cfl-s1 (fully glued down)

Moisture Content 7% (+/-2%)
Hardness Rating 34-41H

Additional Information

UKTR Compliance Yes

Grading Information

Select grade is likely to contain some boards that have a higher number of knots than Prime, and you should also expect some of these knots to be larger in size. There is a possibility of some sapwood and small cracks and filler are likely to be present. A greater level of colour variation in the timber is to be expected.

Installation and Warranty

Atkinson & Kirby recommend that all floors are installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fitting instructions that can be found on our website.

Recommended Care and Maintenance Products*

Installation Method

Care WOCA Natural Soap	
y Care WOCA Oil Refresher Soap	
Months WOCA Maintenance Gel &	
WOCA Intensive Cleaner as primer	
y	

^{*}Remember to patch test any cleaning or finishing products before using on the whole length of your floor.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.