TECHNICAL INFORMATION SHEET

PAR1022 Congaree Smoked Oak Parquet Collection



61/39

Dfl-s1

6-9%

1.8kn

	Product Information	
	Product Name	Congaree Smoked Oak
	Product Code	PAR1022
	Collection	Parquet
	Construction	Engineered
	Size	15 x 90 x 450mm
	Pack Size	0.648m ²
	Grade	Rustic
	Surface	Brushed
	Finish	UV Oiled
	Profile	T&G
	Edge	Bevelled
	Pattern	Herrigbone
	Width	90mm
	Length	450mm
	Thickness	15mm
Additional Information	Wear Layer	3mm
	= Backing	Eucalyptus
JKTR Complicance Yes	Top Layer	Oak
nstallation and Warranty	Installation Method	
A&K recommend all floors should be installed by a competent installer. A&K warranties apply only to floors that have been installed according to our fittings instructions found on our website.	Floated	No
	Secret Nailed	No
	Stuck Down	Yes
	Underfloor Heating	Yes
Grading Information	Technical Information	
Rustic grade has the potential to include all	Formaldehyde Emissions	E1
haracteristics across the majority of boards with knots uppearing in varying sizes as well as colour variation in	Pentachlorophenol Emissions Thermal Conductivity	≤ 5 ppm 0.13W/(mK)
··· - · · ·		

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.

Moisture Content

Hardness Rating

Floors that define your space

Tel: 01695 573234 | Scotland T: 01506 505030 | sales@akirby.co.uk | www.akirby.co.uk

the timber to be expected. Sapwood is possible, checks Slip Resistance PTV

that are likely to be present will be filled in a colour to Fire Classification

complement the natural look of the timber.