TECHNICAL INFORMATION SHEET

CLA1001 Isla Oak Classsic Collection



Isla Oak

Oak



Technical Information

Formaldehyde Emissions	E1
Pentachlorophenol Emissions	0.02-0.04mg/L
Thermal Conductivity	0.1-0.12W/(M.K)
Slip Resistance PTV	62/39
Fire Classification	Dfl-s1
Moisture Content	6-8%
Hardness Rating	2H

Grading Information

Rustic grade has the potential to include all characteristics across the majority of boards with knots installed by a competent installer. Atkinson & Kirby appearing in varying sizes as well as colour variation in warranties apply only to floors that have been the timber to be expected. Sapwood is possible, checks installed according to our fittings instructions that can that are likely to be present will be filled in a colour to be found on our website. complement the natural look of the timber.

Product Information

Product Name

Product Code	CLA1001	
Collection	Classic	
Construction	Engineered	
Size	14 x 125 x RL	
Pack Size	2.2m ²	
Grade	Rustic	
Surface	Smooth	
Finish	Matt Lacquered	
Profile	2G	
Edge	Bevelled	
Pattern	Plank	
Thickness	14mm	
Width	125mm	
_ Length	RL	
Wear Layer	3mm	
Backing	Poplar	

Additional Information

Top Layer

Responsible Certification	PEFC®
UKTR Compliance	Yes

Installation and Warranty

Atkinson & Kirby recommend that all floors are

Installation Method	Recommended Care and Maintenance Products*
---------------------	--

Floated	Yes	For Regular Care	WOCA Master Cleaner
Secret Nailed	No	For Annual Care	WOCA Master Care & WOCA
Stuck Down	Yes		Intensive Cleaner as primer
Underfloor Heating	Yes		

^{*}Remember to patch test any cleaning or finishing products before using on the whole length of your floor.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.