

TECHNICAL INFORMATION SHEET

CLA1006 Harris Oak

Classic Collection



Product Information

Product Name	Harris Oak
Product Code	CLA1006
Collection	Classic
Construction	Engineered
Size	14 x 150 x RL
Pack Size	2.64m ²
Grade	Rustic
Surface	Brushed
Finish	UV Oiled
Profile	2G
Edge	Bevelled
Pattern	Plank
Thickness	14mm
Width	150mm
Length	RL
Wear Layer	3mm
Backing	Poplar
Top Layer	Oak

Technical Information

Formaldehyde Emissions	E1
Pentachlorophenol Emissions	0.02-0.04mg/L
Thermal Conductivity	0.1-0.12W/(M.K)
Slip Resistance PTV	61/39
Fire Classification	Dfl-s1
Moisture Content	6-8%
Hardness Rating	2H

Additional Information

Responsible Certification	PEFC®
UKTR Compliance	Yes

Grading Information

Rustic grade has the potential to include all characteristics across the majority of boards with knots appearing in varying sizes as well as colour variation in the timber to be expected. Sapwood is possible, checks that are likely to be present will be filled in a colour to complement the natural look of the timber.

Installation and Warranty

Atkinson & Kirby recommend that all floors are installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fittings instructions that can be found on our website.

Installation Method

Floated	Yes
Secret Nailed	No
Stuck Down	Yes
Underfloor Heating	Yes

Recommended Care and Maintenance Products*

For Regular Care	WOCA Natural Soap
For Monthly Care	WOCA Oil Refresher Soap
Every 6-12 Months	WOCA Maintenance Gel & WOCA Intensive Cleaner as primer

*Remember to patch test any cleaning or finishing products before using on the whole length of your floor.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.