# TECHNICAL INFORMATION SHEET

# CLA2004 Saddle Oak Classic Collection





#### **Technical Information**

Formaldehyde Emissions	E1
Pentachlorophenol Emissions	0.02 - 0.04 mg/L
Thermal Conductivity	0.1-0.12W/(M.K)
Slip Resistance PTV	62/39
Fire Classification	Dfl-s1
Moisture Content	6-8%
Hardness Rating	2H

#### **Product Information**

Product Name	Saddle Oak
Product Code	CLA2004
Collection	Classic
Construction	Engineered
Size	18 x 150 x RL
Pack Size	1.98m <sup>2</sup>
Grade	Natural
Surface	Smooth
Finish	Lacquered
Profile	T&G
Edge	Bevelled
Pattern	Plank
Thickness	18mm
Width	1 <i>5</i> 0mm
Length	RL
Wear Layer	4mm
Backing	Poplar
Top Layer	Oak

#### Additional Information

UKTR Compliance Yes

#### Grading Information

Natural grade will potentially contain a large number of boards with most characteristics present. Knots are likely to be slightly larger in size than Select and colour variation in the timber to be expected. Sapwood is possible and checks and filler are likely to appear in most boards.

### Installation and Warranty

Atkinson & Kirby recommend that all floors are installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fittings instructions that can be found on our website.

## Installation Method

Floated	Yes
Secret Nailed	Yes
Stuck Down	Yes
Underfloor Heating	Yes

# Recommended Care and Maintenance Products\*

For Regular Care	WOCA Master Cleaner
For Annual Care	WOCA Master Care & WOCA
	Intensive Cleaner as primer

<sup>\*</sup>Remember to patch test any cleaning or finishing products before using on the whole length of your floor.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.