TECHNICAL INFORMATION SHEET

CLA2005 Cairnwell Oak Classic Collection





Technical Information

Formaldehyde Emissions	E1
Pentachlorophenol Emissions	0.02 - 0.04 mg/L
Thermal Conductivity	0.1-0.12W/(M.K)
Slip Resistance PTV	61/39
Fire Classification	Dfl-s1
Moisture Content	6-8%
Hardness Rating	2H

Grading Information

Natural grade will potentially contain a large number of boards with most characteristics present. Knots are likely to be slightly larger in size than Select and colour variation in the timber to be expected. Sapwood is possible and checks and filler are likely to appear in most boards.

Product Information

Cairnwell Oak
CLA2005
Classic
Engineered
18 x 150 x RL
1.98m ²
Natural
Brushed
UV Oiled
T&G
Bevelled
Plank
18mm
150mm
RL
4mm
Poplar
Oak

Additional Information

Responsible Certification	PEFC®
UKTR Compliance	Yes

Installation and Warranty

Atkinson & Kirby recommend that all floors are installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fittings instructions that can be found on our website.

Installation Method

Floated	Yes
Secret Nailed	Yes
Stuck Down	Yes
Underfloor Heating	Yes

Recommended Care and Maintenance Products*

For Regular Care	WOCA Natural Soap
For Monthly Care	WOCA Oil Refresher Soap
Every 6-12 Months	WOCA Maintenance Gel &
	WOCA Intensive Cleaner as primer

^{*}Remember to patch test any cleaning or finishing products before using on the whole length of your floor.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.