TECHNICAL INFORMATION SHEET CLA3002 Brora Limed Oak **Classic Collection**





| Technical Information | |
|-----------------------------|-------------|
| Formaldehyde Emissions | E1 |
| Pentachlorophenol Emissions | <0.1ppm |
| Thermal Conductivity | 0.11W/(M.K) |
| Slip Resistance PTV | 63/33 |
| Fire Classification | Cfl-s1 |
| Moisture Content | 8% (+/-2%) |

| Product Name | Brora Limed Oak | |
|---------------------------|--------------------|--|
| Product Code | CLA3002 | |
| Collection | Classic | |
| Construction | Engineered | |
| Size | 20 x 160 x RL | |
| Pack Size | 1.41m ² | |
| Grade | Rustic | |
| Surface | Smooth | |
| Finish | UV Oiled | |
| Profile | T&G | |
| Edge | Bevelled | |
| Pattern | Plank | |
| Thickness | 20mm | |
| Width | 160mm | |
| _Length | RL | |
| Wear Layer | 6mm | |
| Backing | Birch Plywood | |
| Top Layer | Oak | |
| | | |
| Additional Information | | |
| Responsible Certification | FSC® Mix | |
| UKTR Compliance | Yes | |
| | | |

Product Information

Grading Information

Rustic grade has the potential to include all

appearing in varying sizes as well as colour variation in warranties apply only to floors that have been the timber to be expected. Sapwood is possible, checks installed according to our fittings instructions that can that are likely to be present will be filled in a colour to be found on our website. complement the natural look of the timber.

Atkinson & Kirby recommend that all floors are characteristics across the majority of boards with knots installed by a competent installer. Atkinson & Kirby

Installation and Warranty

| Installation Method | Ilation Method Recommended Care and Maintenance Products* | | and Maintenance Products* |
|---------------------|---|-------------------|----------------------------------|
| Floated | Yes | For Regular Care | WOCA Natural Soap |
| Secret Nailed | Yes | For Monthly Care | WOCA Oil Refresher Soap |
| Stuck Down | Yes | Every 6-12 Months | WOCA Maintenance Gel & |
| Underfloor Heating | Yes | | WOCA Intensive Cleaner as primer |
| | | | |

*Remember to patch test any cleaning or finishing products before using on the whole length of your floor.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.

Floors that define your space

Tel: 01695 573234 | Scotland T: 01506 505030 | sales@akirby.co.uk | www.akirby.co.uk