TECHNICAL INFORMATION SHEET CLA3007 Glenmore Oak Classic Collection



| | Product Information | | | |
|--|-----------------------|---|----------|-------------------------|
| | | Product Name | | Glenmore Oak |
| | | Product Code | | CLA3007 |
| | and and the second | Collection | | Classic |
| | | Construction | | Engineered |
| a contraction to a second | The second | Size | | 20 x 190 x 1900mm |
| | | Pack Size | | 2.17m ² |
| - Contraction | No. X | Grade | | Natural |
| William - 1878 | | Surface | | Smooth |
| and the second s | and the second | Finish | | UV Oiled |
| | | Profile | | T&G |
| | State State | Edge | | Bevelled |
| | The second second | Pattern | | Plank |
| and a settle a | | Thickness | | 20mm |
| | | Width | | 190mm |
| Technical Information | | Length | | 1900mm |
| Formaldehyde Emissions | 0.02-0.04mg/L | Wear Layer | | 6mm |
| Pentachlorophenol Emissions | 0.02-0.04mg/L | Backing | | Poplar |
| Thermal Conductivity | 0.1-0.12W/(M.K) | Top Layer | | Oak |
| Slip Resistance PTV | 63/33 | | | |
| Fire Classification | Dfl-s1 | Additional Information | | |
| Moisture Content | 6-8% | Responsible Certifice | ation | PEFC® |
| Hardness Rating | 2H | UKTR Compliance | | Yes |
| Grading Information | | Installation and Warranty | | |
| Natural grade will potentially contain a large number | | Atkinson & Kirby recommend that all floors are | | |
| of boards with most characteristics present. Knots are | | installed by a competent installer. Atkinson & Kirby | | |
| likely to be slightly larger in size than Select and colour | | warranties apply only to floors that have been | | |
| variation in the timber to be expected. Sapwood is | | installed according to our fittings instructions that can | | |
| possible and checks and filler ar most boards. | e likely to appear in | be found on our web | site. | |
| Installation Method | | Recommended Care and Maintenance Products* | | |
| Floated | Yes | For Regular Care | WOCA No | atural Soap |
| Secret Nailed | Yes | For Monthly Care | WOCA Oi | il Refresher Soap |
| Stuck Down | Yes | Every 6-12 Months | | aintenance Gel & |
| Underfloor Heating | Yes | | WOCA Int | ensive Cleaner as prime |
| | | *Remember to patch test any cleaning or finishing products before using on the will length of your floor. | | |

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.

Floors that define your space

Tel: 01695 573234 | Scotland T: 01506 505030 | sales@akirby.co.uk | www.akirby.co.uk