## TECHNICAL INFORMATION SHEET

## Atkinson & Kirby

## BRE1002 Hossa Oak Breathe

characteristics across the majority of boards with knots

appearing in varying sizes as well as colour variation

in the timber to be expected. Sapwood is possible,

checks that are likely to be present will be filled in a

colour to complement the natural look of the timber.

		Product Name	Hossa Oak
		Product Code	BRE1002
		Collection	Breathe
		Construction	Engineered
		Size	14 x 182 x 2200
• 5///.		Pack Size	2.4m <sup>2</sup>
		Grade	Rustic
		Surface	Brushed
		Finish	Commercial Matt Lacquer
		Profile	5G
		Edge	Bevelled
		Pattern	Plank
		Width	182mm
		Length	2200mm
		Thickness	1.4mm
Additional Information		Wear Layer	3.6mm
Responsible Certification	UKTR Compliant	= Backing	Spruce
EPD	Yes	Top Layer	Oak
LEED	Yes		
UKTR Complicance	Yes		
Installation and Warranty		Installation Method	
A&K recommend all floors should be installed by a		Floated	Yes
competent installer. A&K warranties apply only to		Secret Nailed	Yes
floors that have been installed according to our fittings		Stuck Down	Yes
instructions found on our website.		Underfloor Heating	Yes
Grading Information		Technical Information	
Rustic grade has the potential to include all		Formaldehyde Emissions	E1

**Product Information** 

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.

**Pentachlorophenol Emissions** 

**Thermal Conductivity** 

Slip Resistance PTV

Fire Classification

**Moisture Content** 

**Hardness Rating** 

Not detectable

58/31

Dfl-s1

7% +/- 2

34-41 (Brinell)

 $RT = 0.078 \text{ m}^2\text{K}/\text{W}$ 

\*Cfl-s1 fully glued down