TECHNICAL INFORMATION SHEET

Atkinson & Kirby

BRE1007 Tyresta Oak Breathe



Responsible CertificationUKTR CompliantEPDYesLEEDYesUKTR ComplicanceYes

Installation and Warranty

A&K recommend all floors should be installed by a competent installer. A&K warranties apply only to floors that have been installed according to our fittings instructions found on our website.

Grading Information

Rustic grade has the potential to include all characteristics across the majority of boards with knots appearing in varying sizes as well as colour variation in the timber to be expected. Sapwood is possible, checks that are likely to be present will be filled in a colour to complement the natural look of the timber.

Formaldehyde Emissions

Pentachlorophenol Emissions

Thermal Conductivity

Slip Resistance PTV

Fire Classification

Product Information

Product NameTyresta OakProduct CodeBRE1007CollectionBreatheConstructionEngineeredSize14 x 182 x 2200

Pack Size 2.4m²

Grade Rustic
Surface Brushed

Finish Commercial Matt Lacquer

Edge **Bevelled Pattern** Plank Width 182mm Lenath 2200mm **Thickness** 14mm Wear Layer 3.6mm **Backing** Spruce **Top Layer** Oak

Installation Method

Floated Yes
Secret Nailed Yes
Stuck Down Yes
Underfloor Heating Yes

Technical Information

Formaldehyde Emissions E1

Pentachlorophenol Emissions Not detectable

Thermal Conductivity RT = 0,078 m²K/W

Slip Resistance PTV 58/31

Fire Classification Dfl-s1

*Cfl-s1 fully glued down

Moisture Content 7% +/- 2

Hardness Rating 34-41 (Brinell)

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.