


TECHNICAL INFORMATION SHEET



BRE1015 Kolmarden Oak Breathe



Product Information

Product Name	Kolmarden Oak
Product Code	BRE1015
Collection	Breathe
Construction	Engineered
Size	14 x 182 x 2200
Pack Size	2.4m ²
Grade	Rustic
Surface	Brushed
Finish	Natural Oil
Profile	5G
Edge	Bevelled
Pattern	Plank
Width	182mm
Length	2200mm
Thickness	14mm
Wear Layer	3.6mm
Backing	Spruce
Top Layer	Oak

Additional Information

Responsible Certification	UKTR Compliant
EPD	Yes
LEED	Yes
UKTR Compliance	Yes

Installation and Warranty

A&K recommend all floors should be installed by a competent installer. A&K warranties apply only to floors that have been installed according to our fittings instructions found on our website.

Installation Method

Floated	Yes
Secret Nailed	No
Stuck Down	Yes
Underfloor Heating	Yes

Grading Information

Rustic grade has the potential to include all characteristics across the majority of boards with knots appearing in varying sizes as well as colour variation in the timber to be expected. Sapwood is possible, checks that are likely to be present will be filled in a colour to complement the natural look of the timber.

Technical Information

Formaldehyde Emissions	E1
Pentachlorophenol Emissions	Not detectable
Thermal Conductivity	RT = 0,078 m ² K/W
Slip Resistance PTV	53/22
Fire Classification	Dfl-s1 *Cfl-s1 fully glued down
Moisture Content	7% +/- 2
Hardness Rating	34-41 (Brinell)

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice for third parties. To confirm the latest information please speak to a member of our team.